



RECESSED DOWNLIGHTS (non-dimmable)

Dimensions

PGSCDL06HC

Light source 6x 1W CREE LED
 Beam angle 62.5°
 Materials Alluminium and Plastic
 Power drawn 7 W
 Light output 540lm (white) 414lm (warm white)
 Colour rendering (CRI) 75.8 (white) 82.7 (warm white)
 Colour temp White, Warm White


*** 5 -YEAR GUARANTEE ***



PGSCDL09HC

Light source 9x 1W CREE LED
 Beam angle 60°
 Materials Alluminium and Plastic
 Power drawn 10 W
 Light output 569lm (white) 443lm (warm white)
 Colour rendering (CRI) 75.8 (white) 82.7 (warm white)
 Colour temp White, Warm White



*** 5 -YEAR GUARANTEE ***



PGSCDL12HC

Light source 12x 1W CREE LED
 Beam angle 60°
 Materials Alluminium and Plastic
 Power drawn 12 W
 Light output 775lm (white) 670lm (warm white)
 Colour rendering (CRI) 75.8 (white) 82.7 (warm white)
 Colour temp White, Warm White


*** 5 -YEAR GUARANTEE ***



PGSCDL15HC

Light source 15x 1W CREE LED
 Beam angle 60°
 Materials Alluminium and Plastic
 Power drawn 15 W
 Light output 964lm (white) 803lm (warm white)
 Colour rendering (CRI) 75.8 (white) 82.7 (warm white)
 Colour temp White, Warm White



*** 5 -YEAR GUARANTEE ***



PGSCDL18HC

Light source 18x 1W CREE LED
 Beam angle 60°
 Materials Alluminium and Plastic
 Power drawn 18 W
 Light output 1073lm (white) 856lm (warm white)
 Colour rendering (CRI) 75.8 (white) 82.7 (warm white)
 Colour temp White, Warm White

*** 5 -YEAR GUARANTEE ***



IES files for these products are available on request



*These products are available in
 240V AC or 12V DC (requires
 a 12V power adaptor)*

